

ETL Certified to ANSI/NSF Standards. Sleek, Quiet, Consumer-Friendly Design

ETL Sanitation 2 Series commercial air curtains

#### **ETL SANITATION 2 INNOVATIONS**

- → ETL Certification to ANSI/NSF Standards
- → New low profile durable metal design
- → Low noise level for quiet operation
- → Easy to install
- → Low maintenance and operational costs
- → Standard Color Obsidian Black (Special Colors - Titanium Silver/Pearl White/Stls Steel - \$\$ adder)

# FEATURES IN ALL MARS AIR CURTAINS

- → Maintains consistent interior temperature
- → Minimizes dirt, dust, and fumes
- → Controls flying insects
- → Allows for unobstructed views…enhancing safety
- → Effective environmental control
- → Reduced energy consumption

MODEL SERIES **INSTALLATION HEIGHTS** 

7'-8'

7'-8'

SANITATION, ETL LPN2,N2 NH2

8'-10'

8'-12'

10'-12'

14'-16

12'-16'

12'-30'

# ETL Sanitation 2 Series commercial air curtains

| Model                              | Door Width<br>Inches | Door Height<br>Feet | FULL L<br>115V | .0ad amps/1φ<br>208V/ 230V | Sound Pressure<br>Level (dBA) | Net Wt. LBS.<br>Unheated |
|------------------------------------|----------------------|---------------------|----------------|----------------------------|-------------------------------|--------------------------|
| LoPro 2 - ETL Sanitation Certified |                      |                     |                |                            |                               |                          |
| LPN2 25 Drive-Up                   | 25"                  | 5'                  | 2.4            | 1.2/1.2                    | 49                            | 20                       |
| LPN2 36                            | 36"                  | 7'-8'               | 2.4            | 1.2/1.2                    | 49                            | 32                       |
| LPN2 42                            | 42"                  | 7'-8'               | 2.4            | 1.2/1.2                    | 50                            | 35                       |
| LPN2 48                            | 48"                  | 7'-8'               | 2.4            | 1.2/1.2                    | 52                            | 40                       |
| LPN2 60                            | 60"                  | 7'-8'               | 2.6            | 1.4/1.4                    | 53                            | 48                       |
| LPN2 72                            | 72"                  | 7'-8'               | 2.6            | 1.4/1.4                    | 53                            | 58                       |
| LPN2 84-2                          | 84"                  | 7'-8'               | 4.8            | 2.4/2.4                    | 53                            | 75                       |
| LPN2 96-2                          | 96"                  | 7'-8'               | 4.8            | 2.4/2.4                    | 53                            | 83                       |
| LPN2 108-2                         | 108"                 | 7'-8'               | 5              | 2.6/2.6                    | 54                            | 92                       |
| LPN2 120-2                         | 120"                 | 7'-8'               | 5.2            | 2.8/2.8                    | 54                            | 102                      |
| LPN2 144-2                         | 144"                 | 7'-8'               | 5.2            | 2.8/2.8                    | 54                            | 122                      |
| ETL SANITATION CERTIFIED           |                      |                     |                |                            |                               |                          |
| N2 36                              | 36"                  | 7'                  | 5.1            | 2.5/2.5                    | 66                            | 60                       |
| N2 42                              | 42"                  | 7'                  | 5.1            | 2.5/2.5                    | 66                            | 65                       |
| N2 48                              | 48"                  | 7'                  | 5.1            | 2.5/2.5                    | 66                            | 70                       |
| N2 72-2                            | 72"                  | 8'                  | 10.2           | 5.0/5.0                    | 68                            | 145                      |
| NH2 42                             | 42"                  | 8'                  | 9.0            | 5.0/5.0                    | 70                            | 125                      |
| NH 2 48                            | 48'                  | 8'                  | 9.0            | 5.0/5.0                    | 70                            | 130                      |









#### **VALUE ADDED ACCESSORIES**

→ Switch

→ Brackets

→ Control Packages

→ Control Panels

→ Filters → Colors & Finishes

All accessories have been specifically designed to enhance installation, operations, and performance.

They have been tested and are compatible to work with the appropriate Mars units to ensure that efficiency standards and performance levels are met.

For a comprehensive list of the most commonly specified accessories, please download our full accessory brochure at: marsair.com/accessories

## **ADDITIONAL INFORMATION**

For info on how quickly our units pay for themselves in energy saving, visit:

## marsair.com/ROI

For a demonstration of how air curtains work, see our CFD slides at:

### marsair.com/CFD

For help selecting the right unit for your application, go to:

# marsair.com/configurator

For submittal information, specifications, and manuals, download:

#### marsair.com/techinfo

For air curtains 101, view: marsair.com/introvideo

customer entrances cold storage quard outdoor houses gate houses snack shops bars concession stands vestibules smoking rooms industrial food production areas pool bars outdoor decks walk-in coolers factory/office separation pass-through windows