

# MARS AIR CURTAINS HELP TO KEEP FOODSERVICE ENVIRONMENTS CLEAN, PEST-FREE AND PROFITABLE

# CHALLENGES TO THE FOODSERVICE ENVIRONMENT

- Repeated door and window openings introduce exterior air
- Flying pests, dirt, debris and odors diminish clean
- Energy spend is elevated
- Cold storage temperatures need to stay consistent
- Staff need climatic comfort to keep productivity high
- Increase profitability









Application Images: Above - Fast Food Restaurant Floor Plan; Top Right - Patio Seating; Middle Right - Rear/Garbage Door; Bottom Right - Retail Store Entrance

# MARS PROTECTS ALL OPENINGS

- Receiving Doors
   Keeps refuse-driven flying pests out so foodservice areas stay cleaner
- Cold Storage Box
   Keeps product protected with consistent temperature
- Warewashing Units
   High volume facilities deploy the air curtain to dry products quickly
- Pass-Thru Windows

  Mars provides clean support & heated comfort from wind
- Customer Front Entrances Keeps flying insects out & conditioned air in
- Smoking Rooms
   Eradicate odors and separate fumes from non-smoking areas with Mars barrier support
- Patio Openings
   Even patio openings benefit from Mars protection
- Lavatory & Bathrooms
   Mars UVC™ takes on the toughest odors and amplifies sanitation
- Refuse Areas & Trash Coolers
   Odorous refuse and compactor areas are neutralized with Mars UVC™ that tackles VOCs and strong, lingering odors



STD2 (Standard)



Clean Air (UVC)



EP2 (Extra Power)



BD (WindGuard)

# ENTRY & RECEIVING DOOR & PASS-THRU WINDOWS

# Mounting height up to 7'-8'

• Available in Unheated, Electric, & Hot Water/Steam Heat

LPV2 (LoPro2)

- Variable Speed Controller
- Low Profile

# STD2 (Standard 2)

- Mounting height up to 10'-12'
- Available in Unheated, Electric, & Hot Water/Steam Heat
- AMCA Certified (Unheated & Electric Heat)

### SPECIALTY ENTRY & RECEIVING DOORS

#### PH (Phantom)

- Mounting height up to 10'-16'
- Available in Unheated, Electric, & Hot Water/Steam Heat
- Recessed mount
- AMCA Certified (Unheated & Electric Heat)

# QP (QuietPro™)

- Mounting height up to 10'-12'
- Unheated only
- Low noise

#### Clean Air

- Mounting height up to 10'
- Unheated only
- UVC/UVV, HEPA, & Ionization Filtration

# Sanitation (LPN2/N2/NH2)

- Mounting height up to 7'
- Unheated only
- ETL Sanitation Listed as per NSF/ANSI 37

# MID SIZE DOCK & RECEIVING DOORS

# HV2 (High Velocity 2)

- Mounting height up to 12'-14'
- Available in Unheated, Electric, Hot Water/Steam, & Indirect Fired Gas Heat
- AMCA Certified (Unheated)

# EP2 (Extra Power 2)

- Mounting height up to 14'-16'
- Available in Unheated, Electric, Hot Water/Steam, & Indirect Fired Gas Heat

#### **LARGE DOCK DOORS**

### WMI/WMH (Wind Stopping)

- Mounting height up to 14'-20'
- Available in Unheated, Electric, Hot Water/Steam, & Indirect Fired Gas Heat
- Direct drive motor

# BD (WindGuard)

- Mounting height up to 14'-32'
- Available in Unheated, Electric, Hot Water/Steam, & Indirect Fired Gas Heat
- Belt drive motor

### **SPECIALTY OPTIONS**

WASHDOWN | EXPLOSION PROOF | TAMPER PROOF | COLD STORAGE

# MARS RECOMMENDED ACCESSORIES

# **SWITCHES**

- MECHANICAL
   O COMBO PLUNGER/ROLLER
- MAGNETIC
  - COMMERCIAL SURFACE MOUNTED
     INDUSTRIAL SURFACE MOUNTED



99-014 Combination Plunger/Roller Type

#### **CONTROLLERS**

- MOTOR CONTROL PANELS
   O ADJUSTABLE TIME DELAYS
- SOLID-STATE
  - o SIMPLELINK™ 2 o BASIC CONTROLLERS

J0021
Time Delayed Basic Controller (1/2 HP)

### **MOUNTING BRACKETS**

- OFFSET
- EXTENDED WALL
- TRANSOM



**B0005** Adjustable Combination Mounting Bracket

# **FILTERS**

- WASHABLE ALUMINUM
   1/4" PRESSED (MERV 4)
- THROWAWAY PLEATED
  - o HEPA (99.9%, 0.3 MICRONS)
    - o 1/2" TO 2" PLEATED (MERV 8)



Pressed Frame Aluminum Filter



atmosphere is everything

Mars Air Systems

Air Curtain and Air Door Manufacturer www.marsair.com • (800) 421-1266 • sales@marsair.com



LEARN MORE ABOUT MARS AIR CURTAINS!